


EJECTOR SLEEVES

THIN WALL



STANDARD TOLERANCES		
D	+0.0003 -0.0000	+0.007 -0.000
B	-0.0004 -0.0007	-0.01 -0.02
L	+0.030 -0.000	+1.0 -0.0
N	+0.20 -0.00	+5.0 -0.0
S	±0.01	±0.2
G	+0.000 -0.001	+0.00 -0.02
H	+0.000 -0.010	+0.0 -0.2
T	+0.000 -0.002	+0.0 -0.05
	INCH	METRIC

Material:

- M-2 Core = 58-60 HRC Treatment = Nicklon®
- M-2 Core = 58-62 HRC (Thru Hard)

Other:

Material	Core Hardness	Surface Hardness	Treatment

SLEEVE #1			
Dimension	Tolerance		
D	<input type="checkbox"/> Standard	+	-
B	<input type="checkbox"/> Standard	+	-
L	<input type="checkbox"/> Standard	+	-
N	<input type="checkbox"/> Standard	+	-
S	<input type="checkbox"/> Standard	+	-
G	<input type="checkbox"/> Standard	+	-
H	<input type="checkbox"/> Standard	+	-
T	<input type="checkbox"/> Standard	+	-
Quantity:			

SLEEVE #2			
Dimension	Tolerance		
D	<input type="checkbox"/> Standard	+	-
B	<input type="checkbox"/> Standard	+	-
L	<input type="checkbox"/> Standard	+	-
N	<input type="checkbox"/> Standard	+	-
S	<input type="checkbox"/> Standard	+	-
G	<input type="checkbox"/> Standard	+	-
H	<input type="checkbox"/> Standard	+	-
T	<input type="checkbox"/> Standard	+	-
Quantity:			

E-MAIL TECH@PROCOMPS.COM

CONTACT:	COMPANY NAME:	PHONE #:
REFERENCE #:	ACCOUNT #:	E-MAIL ADDRESS: