





CAM ACTION® 250 SERIES


▶ CAD insertion point



*Minus pre-load.

Technical Information:

- Machine pockets from the common location "X" to the dimensions shown.
- Slide Retainers (SRT-10 or SRTM-04) are installed in the slides on the CA-250-50/CAMM-250-12. Ball Plungers retain the slide in the other sizes.



Inch Standard

CATALOGUE NUMBER	TRAVEL	A Pocket	B Pocket	C Minimum Clearance	D Minimum Clearance	E Pocket	F Pocket	S1	S2	S3	R Pocket Radius	R2	THD SOCKET HEAD CAP SCREWS
CA-250-15	.15	.750	.500	.63	.60	.937	.313	.156	.594	.438	1/8	.03	#4-40 x 3/8
CA-250-31	.31	1.375	.800	1.03	1.03	1.375	.375	.313	1.063	.750	3/16	.03	#8-32 x 7/16
CA-250-50	.50	2.000	1.250	1.50	1.90	2.125	.625	.375	1.625	1.125	1/4	.04	1/4-20 x 5/8

Screws (3) included.


Metric Standard

CATALOGUE NUMBER	TRAVEL	A Pocket	B Pocket	C Minimum Clearance	D Minimum Clearance	E Pocket	F Pocket	S1	S2	S3	R	R2	THD SOCKET HEAD CAP SCREWS
CAMM-250-4	4	20	12	17	16	24	8	4	16	10	3	.4	M3-.5 x 10
CAMM-250-8	8	34	20	27	27	38	9	7	27	19	4	.4	M4-.7 x 12
CAMM-250-12	12	50	32	39	38	53	15	10	40	27	5	1.0	M6-1 x 18

Screws (3) included.

CAM ACTION® ACCESSORIES

250 SERIES INSERTS



Inch Standard

M DC53 / 1.2360 **H** 58-62 HRC
M H-13 / 1.2343 **H** 48-52 HRC

ASSEMBLY CATALOG NUMBER	DC53 / 1.2360 CATALOG NUMBER	H-13 / 1.2343 CATALOG NUMBER	W +.000 -.001	H +.000 -.001	L	C	THD SOCKET HEAD CAP SCREW
CA-250-15	CSE25P-15L2	CSE25H-15L2	.500	.374	2.250	3/8	#4-40 x 1/2
CA-250-31	CSE25P-31L2.5	CSE25H-31L2.5	.800	.749	2.500	1/2	#8-32 x 7/8
CA-250-50	CSE25P-50L4	CSE25H-50L4	1.250	1.249	4.000	3/4	1/4-20 x 1.25

Screw included.

Metric Standard

M DC53 / 1.2360 **H** 58-62 HRC
M H-13 / 1.2343 **H** 48-52 HRC

ASSEMBLY CATALOG NUMBER	DC53 / 1.2360 CATALOG NUMBER	H-13 / 1.2343 CATALOG NUMBER	W -.02 -.03	H -.02 -.03	L	C	THD SOCKET HEAD CAP SCREW
CAMM-250-4	CSE25MMP-4L60	CSE25MMH-4L60	12	10	60	8	M3 - .5 x 12
CAMM-250-8	CSE25MMP-8L80	CSE25MMH-8L80	26	22	80	11	M4 - .7 x 22
CAMM-250-12	CSE25MMP-12L100	CSE25MMH-12L100	32	29	100	15	M5 - .8 x 30

Screw included.






CAM ACTION® ASSEMBLIES SELECTION GUIDE

Progressive's CamActions provide easy installation for moulding and releasing details.
Several sizes and travel configurations are available.

- Advanced materials and treatments for long-lasting production.
- Inserts and pins available in all series.
- For application assistance, please contact tech@procomps.com.



Inch Standards

TRAVEL	OVERALL ASSEMBLY SIZES	CATALOGUE NUMBER	CAMACTION SERIES	PAGE NUMBER
.160"	1.00" X 1.25" X 1.00" H	CA-100	100 Series	C-1
.230"	1.00" X 1.25" X 1.50" H	CA-200	200 Series	C-2
.230"	1.00" X 1.25" X 4.12" H	CA-200L*		
.150"	.50" X .75" X 1.25" H	CA-250-15	250 Series	C-6a
.310"	.80" X 1.38" X 1.75" H	CA-250-31		
.500"	1.25" X 2.00" X 2.75" H	CA-250-50		
.250"	1.50" X 2.25" X 2.25" H	CA-300	300 Series	C-4
.250"	1.50" X 2.25" X 5.79" H	CA-300L*		
.750"	1.50" X 2.63" X 2.63" H	CA-350	350 Series	C-5
1.000"	3.00" X 4.00" X 4.44" H	CA-400	400 Series	G-10

L= Longer Driver or Lock to extend below parting line.

Metric Standards

TRAVEL	OVERALL ASSEMBLY SIZES	CATALOGUE NUMBER	CAMACTION SERIES	PAGE NUMBER
4mm	26 X 32 X 25.4 H	CAMM-100	100 Series	C-1
5.8mm	26 X 32 X 38.1 H	CAMM-200	200 Series	C-2
5.8mm	26 X 32 X 103.2 H	CAMM-200L*		
4mm	12 X 20 X 32 H	CAMM-250-4	250 Series	C-6a
8mm	20 X 34 X 47 H	CAMM-250-8		
12mm	32 X 50 X 68 H	CAMM-250-12		
6.35mm	40 X 60 X 57.7 H	CAMM-300	300 Series	C-4
6.35mm	40 X 60 X 147.4 H	CAMM-300L*		
18mm	40 X 64 X 66.5 H	CAMM-350	350 Series	C-5

L= Longer Driver or Lock to extend below parting line.